

AZ 3 HTE Gravity Spray Gun

- Light and Handy
- High Transfer Efficiency
- Extremely Fine Atomization, tested by the major Paint Producers




CERTIFICATE OF COMPLIANCE








We certify that we have tested the Air Gunsa AZ3 HTE Gravity Spray Gun in accordance with prEN 13966-1 Method 2 - Tests for transfer efficiency and that this spray gun complies with the requirements of the Environmental Protection Act 1990, Part 1 - 1997 Revision as detailed in PG6/34(97), PG6/23(97), PG6/40(94), PG6/41(94).

Transfer efficiencies achieved with the materials detailed in the test report were:

PRIMER	93.8%
SOLID COLOUR	78.4%
BASECOAT	81.5%
CLEAR LACQUER	77.9%

Signed for MIRRC THATCHAM:  M. Smith
Chief Executive

THATCHAM
THE MOTOR INSURANCE
REPAIR RESEARCH CENTRE
Colthrop Way, Thatcham, Berkshire, RG19 4NR U.K.

Model	 Ø mm	 bar	 Nl/min	 ml/min	 mm	 No.	 g
AZ3 HTE AZ3 HTE AV	1.0	2.0	200	80	170	*5110	680
	1.3			150	240	*5113	
	1.5			190	260	*5115	
	1.8	205	260	300	*5118		
	2.0	205	265	310	*5120		
	2.5	3.0	279	424	340	*1400	
2.8	427			350	*3300		
3.0	489			360	*1500		
3.5	490			340	*1600		

Max. Working Pressure: 6.8 bar (98 PSI)

Noise Level (LAeqT) 77.6 dB (A)

Temperature range: 5~40° C

Air nipple: G 1/4"

Fluid nipple: G 1/4"



ANEST IWATA U.K. Ltd.
Unit 10 Little End Road, Eaton Socon,
St. Neots - Cambridgeshire - PE19 8JH
Tel. +44 (0) 1480 405419
Fax: +44 (0) 1480 217610
enquiries@anest-iwata.co.uk
www.anest-iwata.co.uk

Distributed by:

CE **II 2 GX**
declaration of ATEX conformity for use in zone 1 and in zone 2