









AZ3 HTE 2 Gravity Spray Gun

- **Fine finish polished body**
Smooth polished surface makes it easier to clean
- **Ergonomic gun design**
New trigger and ergonomic grip shape to relieve stress on painting
- **Light weight & well balanced body**
Gun head 20-50 g lighter than previous model
- **New air flow valve**
Increased control precision
- **Improved AKULON cup**
Improved paint cup with multi thread construction
- **Pressure assisted cup (new product)**
AirGunsA have added a pressure assisted paint cup system to the high viscosity paint application range
- **Spare parts compatible with previous AZ3 HTE**



Model	 Ø mm	 bar	 Nℓ/min	 mℓ/min	 mm	 No.	 g	
AZ3 HTE 2	1.0	2.0	200	80	180	-	517	
	1.3			140	240	-		
	1.5			160	260	-		
	1.8			205	250	300		-
	2.0	205	300	340	-			
	2.5	3.0	279	450	360	-		
	2.8			291	540	380		-
	3.0			288	560	400		-
3.5	307			600	420	-		
AZ3 HTE HVLP	1.3	1.9	340	150	280	-		
	1.5			185	290	-		
	1.8			215	340	-		
	2.0			240	360	-		

Model	AZ3 HTE 2
Test	Transfer Efficiency according to EN 13966-1
Authority	IPA Fraunhofer Institut
Date	27/03/2008
Transfer efficiencies achieved with the materials detailed in the test report were:	
2K Primer Coat	89 %
Water based Base Coat	79 %
2K Clear Coat	84 %
	
<small>Certification available on www.airgunsa.com</small>	

Max. Working Pressure: 6.8 bar (98 PSI) Noise Level (LAeqT) 77.6 dB (A)
Temperature range: 5-40° C Air nipple: G 1/4" M Fluid nipple: G 1/4" F



declaration of ATEX conformity for use in zone 1 and in zone 2



ANEST IWATA U.K. Ltd.
Unit 10 Little End Road, Eaton Socon,
St. Neots - Cambridgeshire - PE19 8JH
Tel. +44 (0) 1480 405419
Fax: +44 (0) 1480 217610
enquiries@anest-iwata.co.uk
www.anest-iwata.co.uk

Distributed by: