

## NEW 77 Manual Spray Gun



- Low air consumption
- Weight 550 g

### Certificate

The Fraunhofer IPA certifies that the

**ANEST IWATA New 77-0 spray gun**  
fitted with a 1,2 mm nozzle  
applying a gun inlet pressure of 2,0 bar and a pump controlled paint feed  
of 480 g/min of a solvent-base 2-K-Finish for wood

has been tested in accordance to EN 13966-1 (VDMA german technical rule 24 366) and  
found to have a transfer efficiency of 82%.

January 2006

Dipl.-Ing. (FH) S. Paustian  
Responsible Scientist



Certification available on [www.airguns.com](http://www.airguns.com)

Model	Ø mm	bar	Nz/min	ml/min	mm	No.	g
NEW 77 0	1.2	3.5	430	480	445	0	550
NEW 77 1S	1.5		180	255	210	1	
NEW 77 2S	2.0		250	345	255	2	
NEW 77 3S	2.5		325	435	280	3	
NEW 77 1G	1.5		180	285	230	1	
NEW 77 2G	2.0		250	390	290	2	
NEW 77 3G	2.5		325	485	330	3	

Air Nipple: G 1/4"

Fluid Nipple: G 3/8"

Noise Level (LAeqT): 82.1 dB (A)



declaration of ATEX conformity for use in zone 1 and in zone 2